

SYLVANIA

EVO

LED RANGE



SYLPROOF LED

LED waterproof luminaires



The new **Sylproof LED** is a range of weatherproof luminaires developed for applications such as covered car parks, storage areas, industrial environments and under canopy applications.

Sylproof LED delivers impressive performance, with up to 7,270lm (luminaire lumen output on 1,565mm

twin version) as well as high efficiency, will help you comply with Building regulations – up to 102lm/W (on 1,265mm Single version).

Additionally, **Sylproof LED** benefits from a polycarbonate body and diffuser offering IP65 protection against moisture and dust, and an impact rating of IK08.

by **HAVELLS SYLVANIA**

SYLPROOF LED

LED waterproof luminaires

FEATURES

- 662mm, 1,265mm & 1,565mm single and twin weatherproof LED luminaires
- Impressive performance, up to 7,270lm (luminaire lumen output on 1,565mm twin version)
- High efficiency, will help you comply with Building regulations - up to 102lm/W (on 1,265mm Single version)
- Neutral white (4,000K)
- Vandal and heat resistant robust polycarbonate body (IK08)
- UV stabilised polycarbonate body and diffuser
- Linear prisms designed to optimise light output and to reduce glare
- Stainless steel fixing brackets for ceiling mounting
- Energy Class: A++, A+, A
- Extra long life with 50,000hours



Exploded view




Top view



Item number	Description	Length (mm)	Body style	Colour name	Colour temperature (K)	System power consumption (W)	Luminaire lumen output (lm)	Efficacy (lm/W)
662mm								
0047880	SYLPROOF LED 12W 1X18* 4000K	662	Single	Neutral white	4,000	12	1,070	88
0047881	SYLPROOF LED 23W 2X18* 4000K	662	Twin / Double	Neutral white	4,000	23	2,008	86
1,265mm								
0047882	SYLPROOF LED 23W 1X36* 4000K	1,265	Single	Neutral white	4,000	23	2,385	102
0047883	SYLPROOF LED 44W 2X36* 4000K	1,265	Twin / Double	Neutral white	4,000	44	4,357	100
1,665mm								
0047884	SYLPROOF LED 37W 1X58* 4000K	1,565	Single	Neutral white	4,000	37	3,794	101
0047885	SYLPROOF LED 75W 2X58* 4000K	1,565	Twin / Double	Neutral white	4,000	75	7,270	97


*Fluorescent equivalent to LED.

Dimensions (mm)




	L	I	H	F
0047880	662	83	91	390
0047881	662	123	91	390
0047882	1265	83	91	855
0047883	1265	123	91	855
0047884	1565	83	91	955
0047885	1565	123	91	955


Photometric Data




662mm - Single version - 12W




1,265mm - Single version - 23W




1,565mm - Single version - 37W



662mm - Twin/Double version - 23W



1,265mm -Twin/Double version - 44W



1,565mm - Twin/Double version - 75W