

Scimitar

SCIMITAR 625X625 34W 3000K DALI

0047542



Range Features

- 34W LED recessed luminaire
- Scimitar is perfect for office lighting, developed with circulation spaces, offices, meeting rooms and reception areas in mind
- Available with a Acrylic PMMA diffuser
- Available in 600 x 600mm or 625 x 625mm modules
- High performance: delivers 2,833lm (luminaire lumen output), equating to 83lm/W (total system efficiency)
- Available in Warm white (3,000K) and Neutral white (4,000K)
- Energy efficient electronic gear including DALI and 3 hour emergency versions as standard
- Ease of installation through the push-in connector
- Pull-up kit supplied as standard
- Long lifetime: 50,000 hours life at 70% of the original output L70
- Less maintenance is required due to the long lifetime of 50,000hrs
- Energy Class: A++, A+, A
- LED technology provides an energy efficient solution with reduced maintenance costs



PRODUKTÜBERSICHT

Zertifizierungen	CE
Farbtemperatur (K)	3000
Farbe	White
Ra	83
Dimmbar	1% to 100%
EAN-Code	5410288475424
Gehäuse	Powder coated steel
IK-Einstufung	IK02
IP-Einstufung	IP20
Lichtfarbe	Warm white
Leuchtenbetriebswirkungsgrad (%)	100
Montage	Ceiling recessed
Bestellnummer	0047542
Lichtausbeute (Nennwert) (lm/W)	77
Nutzbarer Lichtstrom (Nennwert) (lm)	2613
Technologie	LED
Spannung (V)	220-240
Kompatibel mit Glühlampen der Energieeffizienzklasse:	A++

DATENTABELLE

Scimitar

SCIMITAR 625X625 34W 3000K DALI

0047542

Optische Daten

Umgebungstemperatur für maximalen Lichtstrom (°C)	-10°C to +35°C
Farbtemperatur (K)	3000
Ra	83
Verteilungstyp	Direct
Blendbegrenzung	UGR >19
Lichtfarbe	Warm white
Leuchtenbetriebswirkungsgrad (%)	100
Lichtstrom (Nennwert) (lm)	2613
Nutzbarer Lichtstrom (Nennwert) (lm)	2613

Allgemeine Daten

Mittlere Lebensdauer (Nennwert) (h)	50000
Zertifizierungen	CE
Betriebsgeräteverfügbarkeit	Electronic
Betriebsgerätetyp	Integral
Dimmbar	1% to 100%
EAN-Code	5410288475424
Umwelt	Interior
Allgemeiner Einsatz	Office ,Educatio
Gehäuse	Powder coated steel
Montage	Ceiling recessed
Bestellnummer	0047542

Lange Bezeichnung

34W LED recessed luminaire
 Scimitar is perfect for office lighting, developed with circulation spaces, offices, meeting rooms and reception areas in mind
 Available with a Acrylic PMMA diffuser
 Available in 600 x 600mm or 625 x 625mm modules
 High performance: delivers 2,833lm (luminaire lumen output), equating to 83lm/W (total system efficiency)
 Available in Warm white (3,000K) and Neutral white (4,000K)
 Energy efficient electronic gear including DALI and 3 hour emergency versions as standard
 Ease of installation through the push-in connector
 Pull-up kit supplied as standard
 Long lifetime: 50,000 hours life at 70% of the original output L70
 Less maintenance is required due to the long lifetime of 50,000hrs

Energy Class: A++, A+, A
 LED technology provides an energy efficient solution with reduced maintenance costs

Produktname	SCIMITAR 625X625 34W 3000K DALI
Technologie	LED
Kompatibel mit Glühlampen der Energieeffizienzklasse:	A++

Scimitar

SCIMITAR 625X625 34W 3000K DALI

0047542



Physikalische Daten

Farbe	White
Länge der Ausfräsung (mm)	574
Form der Ausfräsung	Square
Diffusoroberfläche	Opal
Diffusormaterial	Acrylic PMMA
Höhe (mm)	80
IK-Einstufung	IK02
IP-Einstufung	IP20
Inklusive Lampe	Integrated
Länge (mm)	621
Einbautiefe (mm)	80
Reflektoroberfläche	Diffuser
Gewicht (kg)	5.1
Breite (mm)	621

Elektrische Daten

Treiberstrom (mA)	1050
Elektrische Schutzklassen	CLASS I
Glühdrahttest	850°C
Lichtausbeute (Nennwert) (lm/W)	77
Ta-Nennwert	from -10°C to +35°C
Leistungsaufnahme gesamt (W)	34
Spannung (V)	220-240

PHOTOMETRIE



TECHNISCHE ZEICHNUNGEN

Scimitar

SCIMITAR 625X625 34W 3000K DALI

0047542

