

TRANSFORMERS FOR LOW VOLTAGE

ALIMENTATORI E TRASFORMATORI ELETTRONICI PER BASSISSIMA TENSIONE

BRAVO

V 220÷240V

Trasformatori elettronici per lampade alogene a bassissima tensione rotondi tipo "toroidali".
Uso indipendente.

"Toroidal" type round electronic transformers for low voltage halogen lamps for independent use.

SELV equivalent     



MINIBRAVO
cod. RN1100



BRAVO 110 PFS
cod. RN1171



BRAVO 200 PFS
cod. RN1191

Artide	W min. max.	Hz	V _{OUT}	ta °C	tc °C	W	Ø D mm	H mm		
MINIBRAVO	20÷70	50/60	12	-15.. +50	75	Ti,C	72	21	2 - 2	40
BRAVO 110 PFS	 35÷110	50/60	12	-15.. +40	95	Ti,C	88	31	2 - 2	20
BRAVO 200 PFS	100÷200	50/60	12	-15.. +50	85	Ti,L,C	101	40	2 - 4	20

MICRO

V 220÷240V

Trasformatori elettronici di dimensioni ridotte per lampade alogene a bassissima tensione, entrata e uscita sullo stesso lato. Uso indipendente.

Electronic transformers for independent use on very low voltage lamps. Approved according to electric appliances standard. Reduced dimensions and weight.

SELV equivalent     



MICRO 60 PFS
cod. RN1608



MICRO 105 PFS
cod. RN1625

Artide	W min. max.	Hz	V _{OUT}	ta °C	tc °C	W	LPH mm		
MICRO 60 PFS	 10÷60	50/60	12	-15.. +40	80	C	103X31X21	2 - 2	25
MICRO 105 PFS	 20÷105	50/60	12	-15.. +55	80	C	124X39X21	2 - 2	25

HOLE

V 220÷240V

Trasformatori elettronici per lampade alogene a bassissima tensione rotondi compatti. Da incorporare.
Built-in Compact round electronic transformers for low voltage halogen lamps.

SELV equivalent    



MINIHOLE
cod. RN1670



HOLE 60C PF
cod. RN1664/C



HOLE 70 PFS
cod. RN1664

HOLE 105 PFS
cod. RN1672

Artide	W min. max.	Hz	V _{OUT}	ta °C	tc °C	W	Ø D mm	H mm		
MINIHOLE	 20÷60	50/60	12	-15.. +45	90	L,C	52.5	17	2 - 2	25
HOLE 60C PF *	 20÷60	50/60	12	-15.. +45	80	Ti,C	53	22	2 - 2	25
HOLE 70 PFS	 20÷70	50/60	12	-15.. +40	85	L,C	53	22	2 - 2	25
HOLE 105 PFS	 35÷105	50/60	12	-15.. +40	88	L,C	70	22	2 - 2	25

* Dimmable with external potentiometer (4,7Mohm - RQ8204)