

LCBI 25W 700mA BASIC phase-cut SR (89800307), 230V/50Hz

Values for dimmers at full load

Product name	Article number	Dimmer type ¹	Control gear per dimmer	Noise rating ²	Flicker rating ³	Other issues ⁴	Rating summary ⁵
Amacher 03 5012 60- 600w	435 HAN	leading	1-12	4	1		adviseable
B-Ticino Magic SM9350S	SM9350S	leading	1-6	3	1		adviseable
Bull B6 GD100	G07D101	leading	1-10	3	1		adviseable
Busch & Jaeger 2247 U 500w/VA	2247-500	leading	1-10	3	1		adviseable
Busch & Jaeger 6513U-102 40-420w/VA	6513 U-102	trailing	1-8	2	1	Poor dim depth	not good
Busch-Jaeger 6523U	6512-0-0306	leading	1-2	3	1		adviseable
Busch-Jaeger 6524U	6512-0-0311	leading	1-2	2	1		average
CHiNT NEW 7-C30510	121227E7	leading	1-10	3	1		adviseable
CLIPSAL 32E 450 UDM	32E450UDM	trailing	1-9	2	1		adviseable
CLIPSAL 32E 450CFLDM	32E450CFLDM	trailing	1-9	2	1		adviseable
CLIPSAL 32E 450LM	32E450LM	leading	1-9	3	1		adviseable
CLIPSAL 32E 450TM	32E450TM	trailing	1-9	2	1		adviseable
CLIPSAL 60TDM SaturnOneTouch	4061TD	trailing	1-7	2	1		adviseable

CLIPSAL C Bus 2 L5508D1A	10871212	leading	1-4 x 8 channel	4	1	Flicker with 2 converters, removed by ZSL-UP ⁴	adviseable
Crabtree CRO-1w20 60-250w	CRO-1	leading	1-5	3	1		adviseable
D & C XHB 15w-150w		leading	1-3	3	1		adviseable
DUEWI D16601160-300w	D1 66011	leading	1-6	4	1		adviseable
DUEWI ET1 53850 20-300w	ET153850	trailing	1-6	2	1		adviseable
Elko 40 315 VA (315LE)	1471444	trailing	1-6	2	1		adviseable
Elko 400 GL1	1471450	leading	1-8	3	1		adviseable
Feller 30583 40 - 500w	30583	leading	1-10	3	1		adviseable
Feller 40600-Rc-FMI 61 20-300VA	548 290 000	trailing	1-6	2	1		adviseable
Feller 40600-RC-FMI 61 20-600VA	548 270 000	trailing	1-12	2	1		adviseable
Feller 40600-RL-FMI-61 40-600 VA	548 260 000	leading	1-12	3	1		adviseable
FUJIYAMA 600w	FJ159	leading	1-12	3	1	Flicker with 2 converters, removed by ZSL-UP ⁴	adviseable
GET 60w-400w	08-07-17	leading	1-8	3	1		adviseable
GET Transformer 60-400VA	07-07-26	leading	1-8	3	1	Flicker with 2 converters, removed by ZSL-UP ⁴	adviseable

JUNG 225 TDE Tronic Dimmer 20-525w	225 TDE	trailing	1-10	2	1		adviseable
KLEIN K513/UX K513/UX20325w	K513/UX	trailing	1-6	2	1	Poor dim depth	not good
KOPP 80.33 40w-400w	059413051	leading	1-8	4	1		adviseable
KOPP 80.7820-275w	807813081	trailing	1-5	2	1		adviseable
Legrand ADW-ETL4	775903	trailing	1-8	2	1		adviseable
Legrand HPM 400L	21901B	leading	1-8	3	1		adviseable
Legrand HPM 400T	21903B	trailing	1-8	2	1		adviseable
Legrand V8051	V8051	leading	1-12	3	1		adviseable
Lumic LM600	LM600	leading	1-12	3	1		adviseable
OPUS-852-095-20-315w ???	852-095	trailing	1-6	2	1		adviseable
Panasonic Max 300	WEG 57813	leading	1-6	3	1	Flicker with 2 converters, removed by ZSL-UP ⁴	adviseable
PEHA 433 HAB Tronic-Dimmer 20-315w	D 433 HAB O.A.	trailing	1-6	2	1		adviseable
RICHMOND 10w-600w	MP600TE	trailing	1-12	2	1	Poor dim depth	not good
SIEMENS 5TC8 28420.600w 20-525VA	5TC8284	trailing	1-10	2	1		adviseable
Simon 45E101	52120342	leading	1-10	3	1		adviseable

TCL L2.0 (Legrand)		leading	1-12	3	1		adviseable
Tridonic DALI-PCD 300 One4all	86458303	universal	1-6	2	1		adviseable
WICKES 60-400W	070619	leading	1-8	3	1		adviseable

Explanation:

1. Dimmer types: leading, trailing, universal
2. Noise evaluation: 1 (very little noise) → 4 (strong noise).
Noise evaluation was only carried out for full load. Values for minimum load are less critical. For reference refer to full load.
3. Flicker evaluation: 1 (no flicker) → 4 (strong flicker)
4. Other issues: description of the issue.
ZSL-UP is an additional circuit that can improve the dimming behavior of specific lamps.
5. Rating summary: 1 (adviseable) → 2 (average) → 3 (not good) → 4 (not useful)

LCBI 25W 700mA BASIC phase-cut SR (89800307), 230V/50Hz

Values for dimmers at minimum load

Product name	Article number	Dimmer type ¹	Control gear per dimmer	Noise rating ²	Flicker rating ³	Other issues ⁴	Rating summary ⁵
Amacher 03 5012 60- 600w	435 HAN	leading	1-12		1		adviseable
B-Ticino Magic SM9350S	SM9350S	leading	1-6		1		adviseable
Bull B6 GD100	G07D101	leading	1-10		1		adviseable
Busch & Jaeger 2247 U 500w/VA	2247-500	leading	1-10		1		adviseable
Busch & Jaeger 6513U-102 40-420w/VA	6513 U-102	trailing	1-8		1	Poor dim depth	not good
Busch-Jaeger 6523U	6512-0-0306	leading	1-2		1		adviseable
Busch-Jaeger 6524U	6512-0-0311	leading	1-2		1		average
CHiNT NEW 7-C30510	121227E7	leading	1-10		2	Flicker at turn-on	average
CLIPSAL 32E 450 UDM	32E450UDM	trailing	1-9		1		average
CLIPSAL 32E 450CFLDM	32E450CFLDM	trailing	1-9		1		adviseable
CLIPSAL 32E 450LM	32E450LM	leading	1-9		1		adviseable
CLIPSAL 32E 450TM	32E450TM	trailing	1-9		1		adviseable
CLIPSAL 60TDM SaturnOneTouch	4061TD	trailing	1-7		1		adviseable

LED control gear with different phase-cut dimmers

CLIPSAL C Bus 2 L5508D1A	10871212	leading	1-4 x 8 channel		1	Flicker with 2 converters, removed by ZSL-UP ⁴	adviseable
Crabtree CRO-1w20 60-250w	CRO-1	leading	1-5		1		adviseable
D & C XHB 15w-150w		leading	1-3		1		average
DUEWI D16601160-300w	D1 66011	leading	1-6		1		adviseable
DUEWI ET1 53850 20-300w	ET153850	trailing	1-6		1		adviseable
Elko 40 315 VA (315LE)	1471444	trailing	1-6		1		adviseable
Elko 400 GL1	1471450	leading	1-8		1		adviseable
Feller 30583 40 - 500w	30583	leading	1-10		1		adviseable
Feller 40600-Rc-FMI 61 20-300VA	548 290 000	trailing	1-6		1		average
Feller 40600-RC-FMI 61 20-600VA	548 270 000	trailing	1-12		1		average
Feller 40600-RL-FMI-61 40-600 VA	548 260 000	leading	1-12		1		adviseable
FUJIYAMA 600w	FJ159	leading	1-12		1	Flicker with 2 converters, removed by ZSL-UP ⁴	adviseable
GET 60w-400w	08-07-17	leading	1-8		1		adviseable
GET Transformer 60-400VA	07-07-26	leading	1-8		1	Flicker with 2 converters, removed by ZSL-UP ⁴	adviseable

JUNG 225 TDE Tronic Dimmer 20-525w	225 TDE	trailing	1-10		1		average
KLEIN K513/UX20325w	K513/UX	trailing	1-6		1	Poor dim depth	not good
KOPP 80.33 40w-400w	059413051	leading	1-8		1		adviseable
KOPP 80.7820-275w	807813081	trailing	1-5		1		average
Legrand ADW-ETL4	775903	trailing	1-8		1		adviseable
Legrand HPM 400L	21901B	leading	1-8		1		adviseable
Legrand HPM 400T	21903B	trailing	1-8		1		adviseable
Legrand V8051	V8051	leading	1-12		1		adviseable
Lumic LM600	LM600	leading	1-12		1	Flicker with 2 converters, removed by ZSL-UP ⁴	adviseable
OPUS-852-095-20-315w ???	852-095	trailing	1-6		1		average
Panasonic Max 300	WEG 57813	leading	1-6		1		adviseable
PEHA 433 HAB Tronic-Dimmer 20-315w	D 433 HAB O.A.	trailing	1-6		1		adviseable
RICHMOND 10w-600w	MP600TE	trailing	1-12		1	Poor dim depth	not good
SIEMENS 5TC8 28420.600w 20-525VA	5TC8284	trailing	1-10		1		adviseable
Simon 45E101	52120342	leading	1-10		1		adviseable

TCL L2.0 (Legrand)		leading	1-12		1		adviseable
Tridonic DALI-PCD 300 One4all	86458303	universal	1-6		1		adviseable
WICKES 60-400W	070619	leading	1-8		1		adviseable

Explanation:

1. Dimmer types: leading, trailing, universal
2. Noise evaluation: 1 (very little noise) → 4 (strong noise).
Noise evaluation was only carried out for full load. Values for minimum load are less critical. For reference refer to full load.
3. Flicker evaluation: 1 (no flicker) → 4 (strong flicker)
4. Other issues: description of the issue.
ZSL-UP is an additional circuit that can improve the dimming behavior of specific lamps.
5. Rating summary: 1 (adviseable) → 2 (average) → 3 (not good) → 4 (not useful)